

Page 6, line 9, delete "47" and insert – 46 –.

Page 7, line 20, delete "34" and insert – 24 –.

In the Claims:

Claim 1, line 1, delete "in combination".

Claim 1, lines 5-6, delete "arranged in a configuration to cut a blister from a sheet of substrate".

Claim 2, line 1, delete "in combination".

Claim 3 line 1, delete "in combination".

R E M A R K S

This amendment is in response to the office action dated March 27, 2001 wherein the drawings were objected to as well as the specification and the claims were rejected under 35 U.S.C. 112. This is also in response to the office communication dated May 31, 2001.

Enclosed please find a new drawing of Fig. 8 corrected as suggested by the examiner.


The disclosure has been amended to correct all of the informalities pointed out by the examiner.

The rejection of the claims under 35 U.S.C. 112 is believed to have been obviated because the claims have been amended and in a fashion that applicant believes is in accordance with the examiner's suggestions.

Please contact the undersigned if any of the supplied material is not in accordance with the new rules.

Respectfully submitted,

WOODLING, KROST AND RUST

By 

Charles R. Rust, Reg. No. 18,716
216-241-4150


Kenneth L. Mitchell, Reg. No. 36,873
216-241-4150

CERTIFICATE OF MAILING UNDER 37 C.F.R. §1.10

I hereby certify that _____
_____ is being deposited with
The United States Postal Service "Express Mail Post Office to
Addressee "service under 37 C.F.R. §1.10 on _____,
Express Mail Certificate No. _____, and is
addressed to _____, Commissioner of Patents and
Trademarks, Washington, D. C. 20231.

Certificate Under 37 CFR 1.8(a)

I hereby certify that this correspondence is
being deposited this day with the United States
Postal Service postage prepaid as first class
mail in an envelope addressed to: Commissioner
of Patents and Trademarks, Washington D. C.
20231

on 6/20/01


Dated: 6/20/01

w/pepe #6

Serial Number 09/580,411

Version with markings to show changes made.

COMPENSATING BLISTER DIE CUTTER APPARATUS

This invention relates to a die cutter apparatus for severing blisters into individual blisters from a sheet of blisters which has been formed from a deformable transparent or translucent sheet of plastic material by a process known to those skilled in the art.

Blisters which are used in the blister packaging art are conventionally formed from a large sheet of plastic material which is heated and formed around molds to produce a plurality of the blisters as part of an integral sheet of plastic material. Because of the nature of the plastic from which the blisters are formed there is a shrinkage of the sheet upon cooling and the amount of shrinkage is dependent upon the chemical nature of the plastic from which the blisters are formed and is also dependent upon other factors too numerous to mention herein. As a result of the shrinkage, the individual blisters will end up when the sheet is cooled at various distances from each other which is inconsistent as between blisters when they are originally formed about their respective molds. In other words, the finished blisters on the formed sheet, because of the shrinkage referred to above, will have distances from their respective centerlines which is different from the centerlines of the molds used to form the blisters. As a result when it is desired to cut the individual blisters from the integral sheet and since they are varying distances apart, the blister itself will be offset from the flange surrounding it.

Summary of the Invention

The present invention contemplates the construction of a blister die cutter unit which accommodates a cutter for each blister formed on a sheet of plastic material with each blister die cutter unit being movable relative to the other so as to accommodate the shrinkage and relative movement of the blisters formed on the integral plastic sheet. This results in the provision that

the rim or flange around each individual blister will be essentially concentric with the blister itself. This object of the invention will be observed with more particularity after an understanding of the structure and function which will be pointed out hereinafter.

Another object of the present invention is to produce a blister die cutter apparatus which is capable of cutting a plurality of blisters from an integral sheet on which the blisters are formed and producing an individual blister severed from the plastic sheet which is concentric with the rim or flange or ridge which is normally formed with each blister.

Another object of the invention is to provide a cutter apparatus which produces a blister which has a consistent flange about the severed blister which provides for a more reliable ~~blister~~ sealing function when it is subsequently sealed to a card which carries advertising indicia thereon and which carries the product within the blister.

Another object is to provide a blister die cutter apparatus which provides a finished blister which is more pleasing in appearance, more structurally sound and which functions to hold a product in a more reliable fashion to a card or substrate to which it is subsequently sealed.

Brief Description of the Drawings

Other objects and a full understanding of this invention may be had by referring to the following description and claims, taken in conjunction with the accompanying drawings, in which:

Fig. 1 is an isometric view of a plastic sheet which has been formed into a plurality of blisters in this illustrative embodiment the blisters being six in number;

Fig. 2 is a view taken generally along the line 2-2 of Fig. 1;

Fig. 3 is a view taken generally along the line 3-3 of Fig. 1;

Fig. 4 is an isometric view of a blister severed from the sheet of Fig. 1 with the blister die cutter apparatus of the present invention;

Fig. 5 is a plan view of the blister of Fig. 4;

5 Figs. 6 and 7 are views similar to Figs. 4 and 5 but illustrating the defects that may occur in conventional blisters produced with conventional cutting apparatus;

Fig. 8 is an isometric view of the compensating blister die cutter apparatus of the present invention illustrating individual blister die cutter units (for example shown here as six in number) being equally spaced from each other);

10 Fig. 9 is an isometric view similar to Fig. 8 showing the individual blister die cutter units being slightly shifted with respect to each other illustrating how the die cutter apparatus accommodates for the shrinkage and relative movement of the blisters produced on a sheet of plastic material after the blisters are formed;

Fig. 10 is an exploded isometric view of an individual blister die cutter unit illustrated in Figs. 8 and 9;

15 Fig. 11 is an elevational view of an individual blister die cutter of the apparatus taken generally along the line 11-11 of Fig. 12;

Fig. 12 is a plan view Fig. 11;

Fig. 13 is an isometric view of a partially assembled blister die cutter unit shown in Figs. 10-12; and

20 Fig. 14 is an enlarged fragmentary view taken in the same direction as Fig. 11 showing how the adjustment members fit through the holes in the cutter structure.

Detailed Description of the Preferred Embodiment

The drawings illustrate the compensating die cutter apparatus of the present invention illustrated generally by the reference numeral 30 and which is seen in various of the views including Figs. 8 and 9 with the apparatus 30 being made up of (in the illustrated embodiment) six individual blister die cutter units identified by the reference numerals 34, 35, 36, 37, 38 and 39.

The problem which the present invention is designed to solve comes from the nature of the sheets of plastic material illustrated at 20 in Figs. 1-3 from which individual blisters are formed. The blisters in Figs. 1, 2 and 3 are identified by the reference numeral 22.

As is understood in the blister packaging industry, it is normal to form a plurality of blisters 22 on and from a sheet of polymeric material by forming a heated sheet of the polymeric material around individual molds which form the blisters 22. In this process the polymeric material is heated to a substantially high temperature, for example on the order of 400° F which allows the sheet 20 to more easily form over the individual molds and with the assistance normally of a vacuum the individual blisters 22 are formed. The sheet is then cooled and removed from the individual dies resulting in a sheet like that shown in Fig. 1. In the cooling process, a given batch of polymeric sheet material will shrink as it is cooled and will shrink irregularly. This results in the distance from individual center lines of the individual blisters being inconsistent. In most instances after a first group of blisters have been produced from a given batch of the polymeric sheet, the individual shrinkage will be somewhat consistent for subsequent sheets. When a manufacturer next goes to another batch of polymeric material the shrinkage will again, in most cases, be different and as usual inconsistent.

steel rule 54 within the rule slots 52 and keep the inside portion with the cavity in it from falling out. The rule has recesses 60 provided therein which closely straddle the bridges 58. Central holes in the top board, backup plate and bottom board form a cavity 62 to receive the individual blisters 22 during a cutting operation.

5 Threaded members 64 are provided and extend through holes 66 in the backup plate and the top board 50 and are threadably received in threaded holes 68 in the bottom board 44 to hold the top board, backup plate and bottom board together fixedly as a unit.

Adjustment members 70 in the form of threaded members extend through holes 72 in the top board 50, backup plate 47 and bottom board 44 and threadably connect into threaded holes 74 in the base 31. The adjustment members 70 are fixedly secured in the base 31 and are of an outer diameter which is smaller than the diameter of the holes 72 in the top board, backup plate and bottom board. This permits the blister die cutter units to move relative to the base 31. The top board, backup plate, bottom board and associated structure comprise a support member and the member 70 of a smaller diameter than holes 72 amounts to a lost motion connection connecting the support member to the base 31.

The construction of each of the blister die cutter units 34-39 as shown in Figs. 8 and 9 is identical and each is mounted to the base 31 in the same fashion. Fig. 8 illustrates the blister die cutter units 34-39 mounted on the base with identical spacing between the edges of the units. This identical spacing has been indicated by the reference numeral 77.

20 This spacing as a matter of example only may be on the order of 1/16" to 1/8". Fig. 14 is an enlarged fragmentary view showing the members 70 and their position in openings 72 and as

depicted in Fig. 8. In order that a die cutting operation be accomplished, the sheet 20 of blisters 22 as illustrated in Fig. 1 is brought into position in the Fig. 8 condition so that a given blister 22 fits into a given die cutter unit 34-39. Any shrinkage or movement of a blister 22 relative to another blister on the sheet 20 because of shrinkage is accommodated when a blister is pushed
5 down into the cavity 62 of a given unit which causes that unit to shift so that a given blister fits into a given cavity in a symmetrical fashion. This causes the various die cutter units 34-39 to shift relative to each other as illustrated in Fig. 9 which positions each blister in a cavity of a given die cutter unit 34-39 in a symmetrical fashion so that a product like that illustrated in Figs. 4 and 5 is produced when the cutting operation is effected.

10 The cutting operation is conventional in nature in that the apparatus as illustrated in Figs. 8 and 9 is mounted on the platen of a die cutting mechanism and the platen is normally moved toward a planar surface. This causes the cutting edges 56 of the individual die cutter units to sever the blisters 22 from the sheet 20. When the operation is completed and the platen is moved away, the ejection rubber 53 of each unit 34-39 ejects the cut blisters from around the
15 steel rules 54.

It will thus be seen that the present invention accomplishes the objects hereof in that the cutting units are constructed and mounted in such a fashion that they accommodate any possible and reasonable shrinkage of sheet 20 from which the blisters are formed thereby enabling the blisters 22 to symmetrically reside in the cavities of the units. The blisters are severed in such a
20 fashion that a symmetrical rim ²⁴~~54~~ is produced on the blisters.

Although this invention has been described in its preferred form with a certain degree of

What is claimed is:

(Amended)

1. A compensating blister die cutter apparatus including ~~[in combination]~~

a base member,

at least first and second blister die cutter units supported by said base member,

5 each said blister die cutter unit comprising a

a support member carrying a steel rule die ~~[arranged in a configuration to cut a~~

~~blister from a sheet of substrate]~~

a lost motion connection connecting said support member to said base

member permitting relative lateral movement of each die cutter unit

10 relative to said base member.

(Amended)

2. A compensating blister die cutter apparatus including ~~[in combination]~~

a base member,

at least first and second blister die cutter units supported by said base member,

each said blister die cutter unit comprising

15 a bottom board, a backup plate positioned on said bottom board,

a top board positioned on said backup plate,

a rule slot in said top board,

a steel rule in said rule slot and having a cutting edge,

a cavity formed in the central portion of said bottom board, backup plate and top board

20 as assembled,

threaded members connecting the bottom board, backup plate and top board together

to move as a unit,

vertical holes extending through the connected bottom board, backup plate and the top

board and having a diameter of a given dimension,

adjustment members extending through said vertical holes and being threaded into

5 said base member,

said adjustment members having a smaller diameter than said given dimension thus

permitting lateral movement of said connected bottom board, backup plate and top board

relative to said base member.

(Amended)

3. A compensating blister die cutter apparatus including ~~in combination~~

10 a base member,

at least first and second blister die cutter units supported by said base member,

each said blister die cutter unit comprising a top board,

a rule slot in said top board,

a steel rule in said rule slot and having a cutting edge,

15 a cavity formed in the central portion of said top board,

vertical holes extending through said top board and having a diameter of a given

dimension,

adjustment members extending through said vertical holes and being connected to

said base member,

20 and said adjustment members having a smaller diameter than said given dimension.